

21" ETSI Series

Complies with the ETSI EN 300 119-3 standard

Standard equipment

- Glass front door
- Blind rear door
- Blind side panels with ventilation slots
- Double pair of 21" uprights

Models

SU*	U**	Height x Width x Depth	Reference***
42	24	1177.5 x 600 x 600 mm	334-D6624-21
42	24	1177.5 x 600 x 300 mm	334-D6324-21
83	47	2200 x 600 x 600 mm	334-D6647-21
83	47	2200 x 600 x 300 mm	334-D6347-21



* **SU** = number of steps according to the ETSI standard
 ** **U** = number of units 19" usable with 19" uprights (optional)
 *** **Colors** : Grey / Black (add «N» at the end of the reference)

Accessories

Description	Reference
Fix shelf, 200mm deep, 2 point xing, 1U-21" ETSI, capacity load: 15kg	334-F9292-21
1U-21" ETSI cable management panel, with 4 short plastic rings	334-F9030-21
Extensible shelf, 427x755mm deep, 4 point xing, 1U-21" ETSI, capacity load: 30kg	334-F9008-21
Fix shelf, 400mm deep, 2 point xing, 2U-21" ETSI, capacity load: 25kg	334-F9001-21
Fix shelf, 470mm deep, 4 point xing, 2U-21" ETSI, capacity load: 80kg	334-F9100-21
1U-21" ETSI blank panel	334-F9012-21
2U-21" ETSI blank panel	334-F9102-21
3U-21" ETSI blank panel	334-F9013-21
Pair of inch reducers: 21"-> 19" -1U, with screws	334-F9331
Pair of inch reducers: 21"-> 19" -2U, with screws	334-F9332
Pair of inch reducers: 21"-> 19" -3U, with screws	334-F9333
Pair of 47U-19" uprights for ETSI cabinets	334-F9070-21
Pair of 24U-19" uprights for ETSI cabinets	334-F9074-21
Wall xing bracket. It is necessary to x cabinets with a depth of 300 mm, in particular those of 2000 mm in height in installations that do not provide other safety solutions.	334-F9977
Closing bottom and/or roof plate for ETSI cabinets 600mm deep	334-F9978
Closing bottom and/or roof plate for ETSI cabinets 300mm deep	334-F9979
Galvanized back plate for telephone and electric devices-21" - h.1000mm	334-F9996
Galvanized back plate for telephone and electric devices-21" - h.2000mm	334-F9997